

METHOD AND APPARATUS TO REDUCE CROSSTALK IN A MIMO COMMUNICATION SYSTEM

BACKGROUND

A multiple input multiple output (MIMO) system may involve treating a plurality of communications mediums as a single communication channel. For example, a MIMO system may treat a plurality of individual twisted-pair copper wires bundled into a single cable as a single communications channel having multiple inputs and multiple outputs. Information transmitted over a given copper wire, however, may be susceptible to interference from information transmitted over an adjacent copper wire. This condition is typically referred to as "crosstalk." The performance of a MIMO system may be significantly increased by reducing the amount of crosstalk in the MIMO channel. Consequently, there may be need for improvements in such techniques in a device or network.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter regarded as the embodiments is particularly pointed out and distinctly claimed in the concluding portion of the specification. The embodiments, however, both as to organization and method of operation, together with objects, features, and advantages thereof, may best be understood by reference to the following detailed description when read with the accompanying drawings in which:

FIG. 1 illustrates a MIMO system suitable for practicing one embodiment;

FIG. 2 illustrates a block diagram of a CFM (CFM) in accordance with one embodiment;

FIG. 3 is a block flow diagram of the programming logic performed by a CFM in accordance with one embodiment; and

FIG. 4 is a graph illustrating the performance of a CFM in accordance with one embodiment.

DETAILED DESCRIPTION

The embodiments may comprise a method and apparatus to suppress crosstalk in a communication system utilizing a full duplex communications medium such as copper wire twisted pairs, radio-frequencies (RF), and other mediums. Examples of crosstalk may be far end crosstalk (FEXT) or near end crosstalk (NEXT) (collectively referred to herein as “crosstalk”). The embodiment may be directed to a crosstalk suppression scheme to reduce or cancel crosstalk for a multiple input multiple output (MIMO) full duplex wired or wireless communication system using either inter-symbol interference (ISI) or non-ISI channels. This embodiment may suppress crosstalk in band-limited channels, and also separates the crosstalk suppression problem from the equalization that provides the ultimate crosstalk suppression level. As a result, the embodiment may use the same equalizer for all outputs of the crosstalk suppression scheme.

Numerous specific details may be set forth herein to provide a thorough understanding of the embodiments of the invention. It will be understood by those skilled in the art, however, that the embodiments of the invention may be practiced without these specific details. In other instances, well-known methods, procedures, components and circuits have not been described in detail so as not to obscure the embodiments of the invention. It can be appreciated that the specific structural and

functional details disclosed herein may be representative and do not necessarily limit the scope of the invention.

It is worthy to note that any reference in the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

Referring now in detail to the drawings wherein like parts are designated by like reference numerals throughout, there is illustrated in FIG. 1 a system suitable for practicing one embodiment. FIG. 1 is a block diagram of a system 100. System 100 may comprise a plurality of network nodes. The term “network node” as used herein may refer to any node capable of communicating information in accordance with one or more protocols. Examples of network nodes may include a computer, server, switch, router, bridge, gateway, personal digital assistant, mobile device, call terminal and so forth. The term “protocol” as used herein may refer to a set of instructions to control how the information is communicated over the communications medium.

In one embodiment, system 100 may communicate various types of information between the various network nodes. For example, one type of information may comprise “media information.” Media information may refer to any data representing content meant for a user. Examples of content may include, for example, data from a voice conversation, videoconference, streaming video, electronic mail (“email”) message, voice mail message, alphanumeric symbols, graphics, image, video, text and so forth. Data from a voice conversation may be, for example, speech information, silence periods, background noise, comfort noise, tones and so forth. Another type of information may comprise “control information.” Control information may refer to any

data representing commands, instructions or control words meant for an automated system. For example, control information may be used to route media information through a network, or instruct a network node to process the media information in a predetermined manner. Both the media and control information may be communicated in a data stream between two or more endpoints. The term “data stream” as used herein may refer to a collection of bits, bytes or symbols sent in series during a data communication session.

In one embodiment, one or more communications mediums may connect the nodes. The term “communications medium” as used herein may refer to any medium capable of carrying information signals. Examples of communications mediums may include metal leads, semiconductor material, twisted-pair wire, co-axial cable, fiber optic, RF spectrum, and so forth. The terms “connection” or “interconnection,” and variations thereof, in this context may refer to physical connections and/or logical connections.

In one embodiment, for example, the network nodes may be connected by communications mediums comprising RF spectrum for a wireless network, such as a cellular or mobile system. In this case, the network nodes and/or networks shown in system 100 may further comprise the devices and interfaces to convert the signals carried from a wired communications medium to RF signals. Examples of such devices and interfaces may include omni-directional antennas and wireless RF transceivers. The embodiments are not limited in this context.

In one embodiment, the network nodes may communicate information to each other in the form of packets. A packet in this context may refer to a set of information of a limited length, with the length typically represented in terms of bits or bytes. An example of a packet length might be 1000 bytes. The packets may be communicated in

accordance with one or more packet protocols. For example, in one embodiment the packet protocols may include one or more Internet protocols, such as the Transmission Control Protocol (TCP) and Internet Protocol (IP). The embodiments are not limited in this context.

Referring again to FIG. 1, system 100 may comprise a wired or wireless communication system using a MIMO communication channel. In one embodiment, for example, system 100 may comprise a local area network (LAN) operating in accordance with one or more Ethernet based communication protocols as defined by the Institute for Electrical and Electronic Engineers (IEEE) 802.3 series of standards, such as a Gigabit Ethernet 1000Base-T communication system ("Gigabit Ethernet"), an advanced 10GBase-T communication system, and so forth. Although one embodiment may be illustrated in the context of a Gigabit Ethernet system by way of example, it can be appreciated that any type of communication system employing a MIMO channel may be used and still fall within the intended scope of the embodiments.

FIG. 1 may illustrate the structure of Gigabit Ethernet system 100. As shown in FIG. 1, system 100 may comprise network nodes 120 and 122. Network nodes 120 and 122 may each represent processing systems having Gigabit Ethernet device(s). The Gigabit Ethernet devices may be implemented as part of a network interface card (NIC), for example. More particularly, network node 120 may comprise a set of equalizers (1-N) 102, a CFM (CFM) 104, a set of transmitter/receivers ("transceivers") (1-N) 106, and a channel estimator 116. Network node 122 may have a similar structure to network 120, and may comprise a set of equalizers (1-M) 114, a CFM 112, a set of transceivers (1-M) 110, and a channel estimator 118. In a typical implementation, M and N are normally equal, although the embodiments are not necessarily limited in this context. Network nodes 120 and 122 may communicate information between each

other using a MIMO channel 108. Although only two network nodes and one MIMO channel are shown in FIG. 1 for purposes of clarity, it can be appreciated that any number of network nodes and MIMO channels may be used and still fall within the scope of the embodiments.

System 100 may operate to communicate information between network nodes 120 and 122 at communication speeds of approximately 1000 megabits per second (Mbps). The 1000 Mbps full duplex data throughput may be achieved using MIMO channel 108. MIMO channel 108 may comprise, for example, four pairs of twisted pair coppers wires bundled in a Category 5 (CAT-5) cable. Each pair may transmit a 250 Mbps data stream encoded into a 4-dimension 5-level pulse amplitude modulation (4-D PAM-5) signal constellation. In essence, the four pairs of CAT-5 unshielded twisted pair (UTP) wiring may be treated as one channel with four inputs and four outputs. Hence, each network node may contain four similar transceivers, one for each pair of physical wire. For example, each of the transmitters of transceivers 1-N may be paired with a corresponding receiver of transceivers 1-M. Hybrid circuits (not shown) may facilitate bidirectional data transmission on the same wire.

During the initialization of system 100, the paired transceivers may go through a training phase in an attempt to characterize MIMO channel 108. Channel estimators 116 and 118 may control or assist in the training phase. Signals may be communicated between the respective transmitters and receivers, and at least one characteristic of MIMO channel 108 may be measured, such as channel impulse responses, amplitude levels, shapes of the signals, signal distortion, crosstalk impulse responses, temporal shifts and delays, and so forth. The communicated signals received by the receiving device are predetermined signals, and deviancies from the expected values are noted by the receiving device.

One factor that can result in deviancies is crosstalk noise. Crosstalk noise, such as FEXT noise, may result when the energy from a signal in one communications path or data stream interferes with the signal in one or more other communication paths or data streams. That is, crosstalk noise represents unwanted coupling between two or more transmitting pairs as the signal propagates from the transmit end of the pair to the receiving end. Crosstalk noise may impact the ability of the receiver to decode a particular data stream, and also may impair the speed or bandwidth for MIMO channel 108.

In one embodiment, channel estimators 116 and 118 may be used to perform channel characterization for MIMO channel 108 in an effort to estimate potential crosstalk noise. Channel estimators 116 and 118 may estimate a plurality of channel impulse response values for MIMO channel 108. Channel estimators 116 and 118 may estimate a channel impulse response value between each transmitter and each receiver. Consequently, for a MIMO system with N transmitters and M receivers, $N \times M$ impulse responses should be obtained after the training phase. These channel impulse responses may then be used to construct a MIMO channel impulse response matrix. Accordingly, channel estimators 116 and 118 pass the channel impulse response values to CFMs 104 and 112, respectively. CFMs 104 and 112 may use the channel impulse response values to assist in creating an appropriate filter for suppressing the crosstalk noise.

In one embodiment, for example, CFMs 104 and 112 may receive the values from channel estimators 116 and 118, respectively. Each CFM may use the estimated MIMO channel impulse responses provided by the channel estimators to synthesize or create a filter to assist in reducing or canceling crosstalk noise at a receiver coupled to MIMO channel 108. Therefore, in one embodiment the filter may be synthesized after

the training phase. CFMs 104 and 112 may be discussed in more detail with reference to FIG. 2.

FIG. 2 may illustrate a CFM in accordance with one embodiment. FIG. 2 may illustrate a CFM 200. CFM may be representative of, for example, CFMs 104 and 112. In one embodiment, CFM 200 may comprise one or more modules. For example, in one embodiment 200 may comprise a channel impulse response (CIR) matrix generator 202, a crosstalk suppression filter (CSF) matrix generator 204, and a filter 206. Although these modules may be described by way of example, it can be appreciated that a greater or lesser number of modules may be used and still fall within the scope of the embodiments. Further, although the embodiment has been described in terms of “modules” to facilitate description, one or more circuits, components, registers, processors, software subroutines, or any combination thereof could be substituted for one, several, or all of the modules.

The embodiments may be implemented using an architecture that may vary in accordance with any number of factors, such as desired computational rate, power levels, heat tolerances, processing cycle budget, input data rates, output data rates, memory resources, data bus speeds and other performance constraints. For example, one embodiment may be implemented using software executed by a processor. The processor may be a general-purpose or dedicated processor, such as a processor made by Intel® Corporation, for example. The software may comprise computer program code segments, programming logic, instructions or data. The software may be stored on a medium accessible by a machine, computer or other processing system. Examples of acceptable mediums may include computer-readable mediums such as read-only memory (ROM), random-access memory (RAM), Programmable ROM (PROM), Erasable PROM (EPROM), magnetic disk, optical disk, and so forth. In one

embodiment, the medium may store programming instructions in a compressed and/or encrypted format, as well as instructions that may have to be compiled or installed by an installer before being executed by the processor. In another example, one embodiment may be implemented as dedicated hardware, such as an Application Specific Integrated Circuit (ASIC), Programmable Logic Device (PLD) or Digital Signal Processor (DSP) and accompanying hardware structures. In yet another example, one embodiment may be implemented by any combination of programmed general-purpose computer components and custom hardware components. The embodiments are not limited in this context.

As shown in FIG. 2, CIR matrix generator 202 may receive one or more measured values (e.g., measured channel impulse responses) from a channel estimator, such as channel estimators 116 and 118. CIR matrix generator 202 may use the measured value(s) to construct a CIR matrix.

In one embodiment, the CIR matrix may represent a description of how a communication medium such as MIMO channel 108 alters the signal that is being transmitted between two endpoints, such as network nodes 120 and 122. With any practical channel the inevitable filtering effect will cause a spreading of individual data symbols passing through the communications channel. The CIR matrix attempts to characterize or describe how the propagation of a transmitted signal induces a signal at the receiver. It is possible to express the channel in terms of an impulse response, that is, the signal that would be received were an impulse to be transmitted. In one embodiment, for example, the CIR matrix may characterize MIMO channel 108 as a generic N -input and M -output MIMO system composed of P -tap finite impulse response (FIR) filters expressed in matrix form. Once the CIR matrix is generated, CIR matrix generator 202 may send the generated CIR matrix to CSF matrix generator 204.

In one embodiment, CSF matrix generator 204 may receive the CIR matrix. CSF matrix generator 204 may generate a CSF matrix using the received CIR matrix. The CSF matrix may represent a matrix filter constructed using the CIR values approximated by the FIR filters. The CSF matrix is synthesized using the CIR matrix in an attempt to reduce or eliminate crosstalk for MIMO channel 108. Once the CSF matrix is generated, CSF matrix generator 204 may send the generated CSF matrix to filter 206.

In one embodiment, filter 206 may receive the CSF matrix. Filter 206 may use the CSF matrix to filter crosstalk noise from one or more data streams communicated using MIMO channel 108. The CIR matrix, CSF matrix and filter 206 may be described in more detail with reference to FIGS. 3 and 4.

The operations of systems 100 and 200 may be further described with reference to FIGS. 3 and 4 and accompanying examples. Although FIGS. 3 and/or 4 presented herein may include a particular programming logic, it can be appreciated that the programming logic merely provides an example of how the general functionality described herein can be implemented. Further, the given programming logic does not necessarily have to be executed in the order presented unless otherwise indicated. In addition, although the given programming logic may be described herein as being implemented in the above-referenced modules, it can be appreciated that the programming logic may be implemented anywhere within the system and still fall within the scope of the embodiments.

FIG. 3 illustrates a programming logic 300 for a CFM in accordance with one embodiment. As shown in programming logic 300, a CIR matrix may be estimated at block 302. A CSF matrix may be created based on the CIR matrix at block 304. The CIR matrix and CSF matrix may have a similar structure and matrix dimension. A

plurality of data streams received over a channel for a MIMO system may be filtered using the CSF matrix to reduce crosstalk at block 306. The data streams may each comprise, for example, an ISI or non-ISI signal. The filtered data streams may then be equalized by one or more equalizers using the same or similar equalization parameters.

In one embodiment, the CIR matrix may be estimated by estimating at least one channel characteristic for the MIMO channel. A plurality of channel impulse response elements may be estimated based on the channel characteristic. The CIR matrix may be created using the channel impulse response elements.

The operation of systems 100 and 200, and the programming logic shown in FIGS. 3 and 4, may be better understood by way of example. As discussed previously, CFM 200 may estimate a CIR matrix, and then synthesize a CSF matrix for use in filtering crosstalk noise from a MIMO channel, such as MIMO channel 108. For purposes of this example, assume a bi-directional Gigabit Ethernet system having a MIMO channel with 4 inputs and 4 outputs, as shown in system 100. Consider the general case of a linear, dispersive, and noisy digital communication MIMO system with m_0 inputs and m_0 outputs. The signals at the j -th channel output ($1 \leq j \leq m_0$) have the standard form:

$$y_i(t) = \sum_{i=1}^{m_0} h_{ij}(t) \otimes s_j(t) + n_i(t) \quad (1)$$

where $y_i(t)$ - i -th channel output, $h_{ij}(t)$ - channel impulse response between the j -th input and the i -th output, $s_j(t)$ - the j -th channel input signal, $n_i(t)$ - noise at the i -th output.

In discrete form the equation (1) may be rewritten as follows:

$$y_i(k) = \sum_{j=1}^{m_0} \sum_{m=0}^{L_{ij}} h_{ij}(m) \cdot s_j(k-m) + n_i(k); \quad (2)$$

where $h_{ij}(m)$ - tap gain coefficients of finite impulse response of the equivalent discrete-time channel between the j -th input and the i -th output, whose memory is denoted by L_{ij} , the $s_j(m)$ $n_i(m)$ $y_i(m)$ - are sampled versions of the $s_j(t)$, $n_i(t)$, $y_i(t)$ respectively.

By grouping the received signals from all m_0 channel outputs into a column vector $\mathbf{y}(t)$ the equation (1) is expressed in matrix form:

$$\mathbf{y}(t) = \mathbf{H}(t) \otimes \mathbf{s}(t) + \mathbf{n}(t), \quad (3)$$

where, $\mathbf{y}(t)$ $m_0 \times 1$ vector of the received signals, $\mathbf{H}(t)$ - is the $m_0 \times m_0$ MIMO channel impulse response matrix, $\mathbf{s}(t)$ - $m_0 \times 1$ vector of the transmitted signals, $\mathbf{n}(t)$ - noise vector.

In discrete form the equation (3) can be written as following:

$$\mathbf{y}(k) = \sum_{m=0}^v \mathbf{H}(m) \mathbf{s}(k-m) + \mathbf{n}(k) \quad (4)$$

where v is the maximum length of all of the $m_0 \times m_0$ channel impulse responses, i.e., $v = \max_{i,j} L_{ij}$. Note that in these notations the non-diagonal elements of the CIR matrix $\mathbf{H}(t)$ represent the undesirable crosstalk impulse responses and introduce the unwanted interference (i.e., crosstalk) into useful signal from the adjacent pairs (or parallel spatial channels for wireless communication system) and these interferences are removed by CFM 200.

In this example, assume that system 100 reduces crosstalk noise by performing the following operations. As an initial matter, the overall channel characteristics of system 100 should be defined. Any given channel estimation technique may be used to define the channel characteristics. The particular channel estimation technique used for a given implementation may be defined by the level of crosstalk suppression desired, which in turn depends on the accuracy properties of estimate.

Once the channel estimation operation is fulfilled, the complete CIR matrix $\hat{\mathbf{H}}(t)$ may be constructed at the receiver end. This matrix may contain a set of CIR matrix values approximated by the FIR filters, which may be represented as follows:

$$\hat{\mathbf{H}}(t) = \begin{pmatrix} \hat{h}_{11}(t) & \cdots & \hat{h}_{1j}(t) & \cdots & \hat{h}_{1m_0}(t) \\ \vdots & \cdots & \vdots & \cdots & \vdots \\ \hat{h}_{i1}(t) & \cdots & \hat{h}_{ij}(t) & \cdots & \hat{h}_{im_0}(t) \\ \vdots & \cdots & \vdots & \cdots & \vdots \\ \hat{h}_{m_01}(t) & \cdots & \hat{h}_{m_0j}(t) & \cdots & \hat{h}_{m_0m_0}(t) \end{pmatrix}. \quad (5)$$

To suppress the crosstalk in each channel output, a crosstalk suppression filter $\mathbf{Q}(t)$ may be applied to process the received signals. This filter may be synthesized using the CIR matrix $\hat{\mathbf{H}}(t)$.

The algorithm of the crosstalk filter $\mathbf{Q}(t)$ calculation may comprise several stages. The following operations may calculate the elements $q_{ij}(t)$ $i, j = 1, \dots, m_0$ of the crosstalk suppression filter:

1. CIR matrix $\hat{\mathbf{H}}(t)$ may be transposed. The transpose of the CIR matrix may be calculated by interchanging rows and columns.

2. Each element of the obtained matrix may be substituted on its minor. During a minor calculation the convolution operation is applied instead of the multiplication operation.

3. The sign for the minor values may be determined. The sign for the minor values may change from + (plus) to – (minus) for minors with the odd sum of indexes.

As a result of the above operations, a $m_0 \times m_0$ crosstalk suppression filter(s) may be constructed.

Obtained such way the matrix $\mathbf{Q}(t)$ comprises the crosstalk suppression filter. As shown above, the performance of the crosstalk suppression filter may rely upon the measured channel characteristics. Assuming perfect channel knowledge, CFM 200 may completely eliminate crosstalk noise from MIMO channel 108. In the noise-free channel the output of the crosstalk suppression filter can be written as:

$$\mathbf{x}(t) = \mathbf{Q}(t) \otimes \mathbf{y}(t) = \mathbf{Q}(t) \otimes \mathbf{H}(t) \otimes \mathbf{s}(t) = \mathbf{G}(t) \otimes \mathbf{s}(t) \quad (6)$$

where $m_0 \times m_0$ matrix filter $\mathbf{G}(t)$ has the diagonal form with the same elements $g(t)$ on the main diagonal. Therefore the outputs of the matrix crosstalk suppression filter are crosstalk-free signals:

$$x_j(t) = g(t) \otimes s_j(t). \quad (7)$$

To further describe the operation of system 100, consider a lesser complex case of a MIMO system having two inputs and two outputs, without noise. In this case equation (1) gives the relationship between input and output signals in the form

$$\begin{aligned} y_1(t) &= h_{11}(t) \otimes s_1(t) + h_{12}(t) \otimes s_2(t); \\ y_2(t) &= h_{21}(t) \otimes s_1(t) + h_{22}(t) \otimes s_2(t); \end{aligned} \quad (8)$$

The CIR matrix may be represented as $\mathbf{H}(t) = \begin{bmatrix} h_{11}(t) & h_{12}(t) \\ h_{21}(t) & h_{22}(t) \end{bmatrix}$. Assuming perfect

channel estimation, the crosstalk suppression filter may be represented as

$$\mathbf{Q}(t) = \begin{bmatrix} h_{22}(t) & -h_{12}(t) \\ -h_{21}(t) & h_{11}(t) \end{bmatrix}. \quad \text{The output signals of this filter may be described by the}$$

following equation:

$$\begin{aligned} x_1(t) &= [h_{22}(t) \otimes h_{11}(t) - h_{12}(t) \otimes h_{21}(t)] \otimes s_1(t) \\ x_2(t) &= [h_{11}(t) \otimes h_{22}(t) - h_{21}(t) \otimes h_{12}(t)] \otimes s_2(t) \end{aligned} \quad (9)$$

As seen from equation (9), the output signals may be crosstalk-free signals. Note that the complete impulse responses of both outputs are approximately equal. This means that the same equalizers may be applied at the output of the crosstalk suppression filter.

FIG. 4 is a graph illustrating the performance of a CFM in accordance with one embodiment. FIG. 4 may illustrate the performance of a CFM using a MIMO channel comprising unshielded twisted pair copper medium CAT-5 cable. FIG. 4 was plotted for an Ethernet LAN system having 4 pairs of twisted pair cable. In such a system, free transmitters may simultaneously induce crosstalk at the receiver end. A curve 402 illustrates the total crosstalk to useful signal ratio before using a CFM. A curve 404 illustrates the total crosstalk to useful signal ratio after using a CFM. As illustrated by FIG. 4, the use of a CFM provides crosstalk suppression such that the residual crosstalk noise is less than the channel noise floor.

While certain features of the embodiments of the invention have been illustrated as described herein, many modifications, substitutions, changes and equivalents will now occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the embodiments of the invention.